

**Construction:**

Body:	Fabricated 'Zincseal' sheet, powder coated white.
Grill:	Extruded aluminium, natural anodised outlet.
Motor/Fan:	Fractional horsepower, shaded pole motor with tangential, "barrel" fan.
Element:	Nickel Chromium, helical wound wire, supported on ceramic formers with a metal surround, incorporating fibreglass supporting cordage.
Thermostat:	Single pole, pre-set type.
Thermal Protection:	Primary:- Self-resettable mechanical cutout. Secondary:- Non-resettable thermal fuse.
Wiring:	150 Degree, silicon wire with (120°c) insulating "Boots" in all high temperature areas.
Fasteners:	Zinc passivated.

Dimensions

Width:	448mm
Height:	415mm
Depth:	110mm

Suggested mounting height : 1800mm - 2500mm

Features

- Easy to replace thermal fuse
- Pre-set thermostat.
- Surface mounting.
- Available in 1.6, 2.4, 3.0, 3.5 & 4.5 kw
- Practical, functional design.
- Full electrical approval
- Ideal for schools, public halls etc. where operator responsibility is limited and energy conservation is important.

Optional:

- HM7A, Remote Control Box with variable thermostat and '3 hr to Off' timer.
- HM7B, Remote Control Box with pre-set thermostat and '3 hr to Off' timer.

Distributed by:


Models Available:

KW	Catalogue Number	Product Code
1.6	HM7/16	3550 00 001
2.4	HM7/24	3550 00 002
3.0	HM7/3	3550 00 006
3.5	HM7/35	3550 00 003
4.5	HM7/45	3550 00 004

Method of Operation

Air is drawn through the top grill by a tangential fan, past the thermostat, through the heating element and out the bottom grill creating a continuous cycle of warm air into the room. The heater is automatically controlled by a preset thermostat installed within the unit. This thermostat cycles the heat output from high to low element to achieve an overall consistent, comfortable room temperature.

The heater is designed without manual temperature control to ensure the room temperature cannot be tampered with. For greater secure control, the Highmount can be ordered with one of two types of Remote Control Boxes (refer options). These Remote Control Boxes allow the heater to operate for up to three hours at a preset temperature, or at a manually controlled temperature, before turning off.

Distributed by: