



Construction:

Body:	Fabricated 'Zincseal' sheet.
Front Cover:	Folded "Zincseal" sheet, powder coated white.
Top Cover:	Polycarbonate white plastic.
Console:	Polycarbonate charcoal plastic.
Side Vents:	Polycarbonate white plastic.
Grill:	Formed MS wire, powder coated black.
Element:	Nickel Chromium, helical wound wire, supported on formers within a metal surround, incorporating fibreglass supporting cordage.
Motor/Fan:	Fractional horsepower, shaded pole, motor with tangential, "barrel" fan.
Thermostat:	Rotary thermostat turns the heater to off when room temperature reached.
Thermal Protection:	Primary:- Self-resetting, mechanical cutout. Secondary - Non-resetting, thermal fuse.
Timer:	Fully programmable, 24 hour, with rotating front face - optional
On/Off Switch:	Rocker type with inbuilt indicator light
Wiring:	150 Degree, silicon wire with (120°C) insulating "boots" in all high temperature areas.
Knobs:	ABS plastic.
Fasteners:	Zinc passivated.

Dimensions

Width:	530mm
Height:	640mm
Depth:	120mm



Features

- Available in 2.4 & 3.5 kw
- Functional, slim-line design
- Full electrical approval
- Economical operation – turns to off when the chosen room temperature is reached
- Top cover for full protection of all controls.

Optional:

- 24 HR, fully programmable timer.

Distributed by:



Models Available:

KW	Catalogue Number	Product Code
WHITE - Thermostat Only		
2.4	OE24W	3350 00 035
3.5	OE35W	3350 00 036
WHITE - c/w Thermostat & 24hr Timer		
2.4	OE24TW	3350 00 037
3.5	OE35TW	3350 00 038

Method of Operation

Air is drawn through the rear of the side mounted vent panels and past the thermostat sensing bulb by a motor coupled to a tangential, 'barrel' fan. The air continues through the element and exits the heater via the bottom front grill creating a continuous cycle of warm air into the room. The air temperature is thermostatically controlled, allowing the heater to turn off and on to maintain the desired room temperature. The optional, 24 hour, fully programmable timer can be set, via its tabs, to achieve any number of On/Off settings, in minimum 15 minute intervals, through any 24 hour period.

Distributed by: