



Construction:

Body:	Fabricated 'Zincseal' sheet.
Front Cover:	Folded "Zincseal" sheet, powder coated white.
Top Cover:	Polycarbonate white plastic.
Console:	Polycarbonate charcoal plastic.
Side Vents:	Polycarbonate white plastic.
Grill:	Formed MS wire, powder coated black.
Element:	Nickel Chromium, helical wound wire, supported on formers within a metal surround, incorporating fibreglass supporting cordage.
Motor/Fan:	Fractional horsepower, shaded pole, motor with tangential, "barrel" fan.
Thermostat:	Rotary thermostat providing High & Low heat output levels to ensure a warm room environment.
Thermal Protection:	Primary:- Self-resetting, mechanical cutout. Secondary - Non-resetting, thermal fuse.
Timer:	Fully programmable, 24 hour, with rotating front face - optional
On/Off Switch:	Rocker type with inbuilt indicator light
Wiring:	150 Degree, silicon wire with (120°c) insulating "boots" in all high temperature areas.
Knobs:	ABS plastic.
Fasteners:	Zinc passivated.

Dimensions

Width:	530mm
Height:	640mm
Depth:	120mm

Features

- Available in 2.4, 3.5 & 4.5 kw
- Functional, slim-line design.
- Full electrical approval
- Two Stage temperature control via rotary thermostat.
- Top cover for full protection of all controls

Optional:

- Stainless steel front with black lid and side vents.
- 24 HR, fully programmable timer.

Distributed by:



Models Available:

KW	Catalogue Number	Product Code
WHITE - Thermostat Only		
2.4	OS24W	3350 00 030
3.5	OS35W	3350 00 031
4.5	OS45W	3350 00 032
WHITE - c/w Thermostat & 24hr Timer		
2.4	OD24TW	3350 00 018
3.5	OD35TW	3350 00 019
4.5	OD45TW	3350 00 020
BLACK/STAINLESS STEEL - c/w Thermostat & 24hr Timer		
2.4	OD24TBSS	3350 00 021
3.5	OD35TBSS	3350 00 022
4.5	OD45TBSS	3350 00 023

Method of Operation

Air is drawn through the rear of the side mounted vent panels and past the thermostat sensing bulb by a motor coupled to a tangential, 'barrel' fan. The air continues through the element and exits the heater via the bottom front grill creating a continuous cycle of warm air into the room. The air temperature is controlled, allowing the element to oscillate between high and low settings depending on the position of the thermostat knob and the temperature chosen. The optional, 24 hour, fully programmable timer can be set, via its tabs, to achieve any number of On/Off settings, in minimum 15 minute intervals, through any 24 hour period.

Distributed by: